



**SELF-CONTAINED DIRECT DRAW**  
1-, 2-, 3- and 4-Door



**DDS84 shown with optional Draft Arm Towers.**

JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS	
DDS36	Single Door Model
DDS60	2-Door Model
DDS84	3-Door Model
DDS108	4-Door Model

*Note: NSF/ANSI Standard 7 Listed for the storage and display of bottled or canned products only.*

**KEY PRODUCT FEATURES AND BENEFITS**

- Energy efficient self-contained R290 Hydrocarbon refrigeration system provides industry leading cooling performance and temperature consistency
- Select from a wide selection of styles in stainless steel or Tarnish Free Brass finishes with 1 to 6 faucets
- Reinforced bumpers on door sills protect frame while loading kegs for life long durability
- 2" Foamed-in-place insulation provides energy savings using Ecomate(tm), a blowing agent that has zero-ozone depletion and zero global warming potential
- End wall compressor and evaporator design increases storage capacity by 14% compared to top mounted designs
- Full stainless steel drainer can be plumbed directly to floor drain
- Anti-sweat heaters in cabinet face prevents condensation from forming on door, extending door gasket life and protecting flooring below from damage or slip hazards
- Choose between solid stainless steel, black vinyl, or customer provided overlay door

**Quick Features:**

- Integrated door locks standard on all units
- Choose compressor mounted on left or right side of cabinet to match your space
- NSF Rated digital controller allows for easy and precise temperature changes
- 6000K white LED lighting
- Choose between Full Length, 6" Chrome, or pull tab style handles
- 1 Year Parts and Labor Warranty, 5 Year Compressor Warranty



**SELF-CONTAINED DIRECT DRAW**  
**1-, 2-, 3- and 4-Door**

MODEL NUMBERS - DDS36, DDS60, DDS84, DDS108

MODEL NUMBERS		DDS36	DDS60	DDS84	DDS108
<b>NUMBER OF DOORS</b>		1	2	3	4
<b>EXTERIOR CABINET DIMENSIONS</b>	<b>Length - in. (mm)</b>	36 (914)	60 (1524)	84 (2134)	108 (2743)
	<b>Depth - in. (mm)</b>	24¾ (629)	24¾ (629)	24¾ (629)	24¾ (629)
	<b>Height - in. (mm)</b>	34⅞ (878)	34⅞ (878)	34⅞ (878)	34⅞ (878)
<b>INTERIOR CABINET DIMENSIONS</b>	<b>Length - in. (mm)</b>	20 (508)	44 (1118)	68 (1727)	92 (2337)
	<b>Depth - in. (mm)</b>	18¾ (476)	18¾ (476)	18¾ (476)	18¾ (476)
	<b>Height - in. (mm)</b>	31 (787)	31 (787)	31 (787)	31 (787)
<b>* INTERNAL VOLUME, Net. Cu. Ft. (liters)</b>		7.4 (210)	16 (453)	24.8 (702)	33.5 (949)
<b>SHIPPING WEIGHT, Lbs. (kg.)</b>		227 (102)	340 (154)	490 (222)	671 (304)
<b>ELECTRICAL SPECIFICATIONS</b>	<b>Electrical Supply</b>	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph
	<b>Running Load Amps</b>	1.8	2.5	4.2	4.2
	<b>Electrical Connection</b>	Cord connected	Cord connected	Cord connected	Cord connected
	<b>Cord Plug Type</b>	NEMA 5-15	NEMA 5-15	NEMA 5-15	NEMA 5-15
	<b>Cord Length</b>	6'5"	6'5"	6'5"	6'5"
	<b>Defrost Initiation</b>	Automatic	Automatic	Automatic	Automatic
	<b>Defrost Type</b>	Off cycle	Off cycle	Off cycle	Off cycle
	<b>Thermostat</b>	Digital control	Digital control	Digital control	Digital control
<b>REFRIGERATION SPECIFICATIONS</b>	<b>Horsepower</b>	1/6	1/5	1/4	1/4
	<b>Refrigerant</b>	R290	R290	R290	R290
	<b>Refrigerant Charge (grams)</b>	90	100	90	90
	<b>Factory Temperature Setting - Refrigerator F (C)</b>	38° (3.3°)	38° (3.3°)	38° (3.3°)	38° (3.3°)
	<b>Temperature Range - Refrigerator F (C)</b>	33°-40° (0.5°-4.5°)	33°-40° (0.5°-4.5°)	33°-40° (0.5°-4.5°)	33°-40° (0.5°-4.5°)
	<b>Condensing Unit Location</b>	Left or Right	Left or Right	Left or Right	Left or Right
	<b>Expansion Device</b>	Capillary tube	Capillary tube	Capillary tube	Capillary tube
	<b>Pull-Out Condensing Unit</b>	Yes	Yes	Yes	Yes
	<b>Front Vented</b>	Yes	Yes	Yes	Yes
<b>PLUMBING</b>	<b>Floor Drain Included</b>	Yes	Yes	Yes	Yes
	<b>Evaporator Condensate</b>	Automatically	Automatically	Automatically	Automatically

\* Note: For keg capacities and layouts, go to [www.perlick.com](http://www.perlick.com).



**SELF-CONTAINED DIRECT DRAW**  
1-, 2-, 3- and 4-Door

MODEL NUMBERS - DDS36, DDS60, DDS84, DDS108

Note: All Dispensing Towers shown are optional and must be ordered separately.

