

Version	FDPLR15I5MB-R / Island 15" (35cm) - Black - 500 CFM
Collection	Design



Photograph is for information purposes only. May not correspond to the selected version

FEATURES AND PROPERTIES

Materials/Finishes	Painted black steel
Technology	SRS Speed reduction system
Control	Electronic control
Ducting type	Extracting/Filtering
Installation type	Island
Lighting	LED 3x1,2 W - 3200 K
Filters	Top filter, removable and washable Charcoal filter

Ducting type	
Dimensions	15 in
Minimum Electric hob distance	21 in
Minimum Gas hob distance	24 in
Notes	Recommended mounting height from cooking surface to hood bottom: 24" - 35"

ELECTRICAL CONNECTION AND CONSUMPTION


Maximum consumption	280 W
Voltage/Frequency	110-120V 60Hz

BLOWER PERFORMANCE

Motor	500 CFM
Minimum sound level	48 dB (A)re1pW I.E.C. 60704-2-13
Maximum sound level	61 dB (A)re1pW I.E.C. 60704-2-13

WEIGHTS AND DIMENSIONS

Gross weight	56 lbs
Net weight	47 lbs
Volume	11 ft
Packaging dimensions	L 40 x H 20 x D24 in



OPTIONAL ACCESSORIES

Code	Description
103050091	FFCHAR3C0BL - Round charcoal filter Ø 6' - Type 6
KACL.798#41F	Remote under-roof motor 950 m3/h
KACL.770#41F	Remote under-roof 1100 m3/h Brushless
KACL.786#41F	Outdoor extractor fan 1000 m3/h
KACL.796#4AF	Outdoor extractor fan 1500 m3/h
KACL.797#4AF	Remote under-roof motor 1300 m3/h

ENGINE SPECIFICATIONS

Motor speed	1	2	3	4
Noise dB(A) re1pW I.E.C. 60704-2-13	48	54	61	67
Capacity	290	380	490	710
Maximum pressure (Pa)	400	450	480	500
Motor power (W)	134	156	180	215
Air outlet	150	150	150	150

CAPACITY / PRESSURE

